



Size (Inches)	System Connection	Diameter (Inches)	Height w/ Base (Inches)	Height w/o Base (mm)	Capacity (Litre)
07x35 to 14x65	2.5" Top	07 to 14	35.6 to 64.6	897 to 1633	20 to 154
16x65 to 18x65	4" Top	16 to 18	64.6 to 66.25	1633 to 1651	185 to 242
21x62 to 36x72	4" Top n Bottom	21 to 36	73.13 to 80.50	1667 to 1790	242 to 999
42x72 to 48x72	6" Top n Bottom	42 to 48	90.12 to 98.54	1854 to 2136	1306 to 3407
63x116 to 63x144	16" Top n Bottom	63	130.44 to 160.18	1946 to 3695	4732 to 6057

- Operating Parameters**
- Maximum Pressure: 150 psi
 - Maximum Temperature: 120° F

Parameters	Design	NSF
Safety factor	04:01	04:01
Minimum burst	600 psi	600 psi
Cycles of test without leakage	250,000	100,000

MULTI PORT VALVE

Use For	Mounting	Size (Inches)	NB (mm)	Colors
Softener	Top (2.5"; 4")	0.75"; 1"; 1.5"	20; 25; 40	Black; White
Softener	Side	0.75"; 1"; 1.5"; 2.5"	20; 25; 40; 65	Black; White
Filter	Top (2.5"; 4")	0.75"; 1"; 1.5"	20; 25; 40	Black; White
Filter	Side	0.75"; 1"; 1.5"; 2"; 2.5"; 3"	20; 25; 40; 50; 65; 75	Black; White



FILTER

Housing	Size	End Connections	MOC
Bag Filter	10"; 20"	1.5"; 2.0"; 2.5"	PP; UPVC; SS 304; SS 316
Commercial	10"; 20"	1"; 1/2"; 3/4"	PP
Industrial	10"; 20"; 30"; 40"	1"; 1/2"; 3/4"	PP; SS 304; SS 316
Jumbo	10"; 20"	1"; 1.5"	PP; SS 304; SS 316
Transparent	10"; 20"	Brass Thread - 3/4"; 1"	PP
Multi Cartridge	10"; 20"; 30"; 40"	0.5" upto 8" as per design	PP; UPVC; SS 304; SS 316

Filter Element	Length	Micron
Bag Filter	10"; 20"	5; 10; 25; 50; 100
Jumbo Pleated (4")	10"; 20"	0.2; 0.45; 1; 5
Jumbo Spun (4")	10"; 20"	5; 10; 25; 50
Jumbo Wound (4")	10"; 20"	0.5; 1; 5; 10; 25; 50
Pleated	10"; 20"	0.2; 0.45; 1; 5
Spun	10"; 20"; 30"; 40"	5; 10; 25; 50
Wound	10"; 20"; 30"; 40"	0.5; 1; 5; 10; 25; 50
Ceramic	10"	0.3; 0.4
Glass Fibre	20"	10

DOSING PUMP

Model	Max Pressure	Max Discharge	Drive
CD	4	10	Solenoid
KA	12	12	Solenoid
KB	10	16	Solenoid
KC	15	100	Solenoid
KM	10	200	Motor
KH	10	1200	Motor



ROTAMETER



Model	Online	Panel Mounted
4" Length (1/2" connection)	100; 300; 600; 1200	100; 300; 600; 1200
7" Length (3/4" connection)	1200; 2400; 3600	1200; 2400; 3600
11" Length (1" connection)	2500; 5000; 7500; 10000	2500; 5000; 7500; 10000
Big Rotameters (2" connection)	1500 - 15000; 2000 - 20000	
Big Rotameters (2 1/2" connection)	3000 - 30000; 4000 - 40000; 5000 - 50000	

GAUGE N SENSOR

Product	Pressure Gauge	Pressure Switch	Floaty
Range	0-7; 0-21; 0-100 (bar)	3; 6; 10; 16; 30 (bar)	3; 5 (mtr)
Dial Size	2"; 2.5"; 4"; 6"	NA	NA
Mounting	Direct; Panel / Back; Bottom	Direct Mounting	NA
MOC	MS; SS 304; SS 316	Brass	PP
End Port	1/4"; 3/8"; 1/2"; 1"	1/4"; 3/8"; 1/2"	NA



MEMBRANE HOUSING

Diameter	Length	Elements	PSI	MOC
2.5"	21"; 40"	1	250 to 400	FRP; SS 304; SS 316
4"	21" to 200"	1; 2; 3; 4; 5	250 to 1000	FRP; SS 304; SS 316
8"	40" to 200"	1; 2; 3; 4; 5	250 to 1000	FRP; SS 304; SS 316



MEMBRANE

Diameter	Length	Type
2.5"	21"; 40"	Tap Water; Brackish
4"	21"; 40"	Water; Sea Water; Hot
8"	40"	Water Sanitisable

Mumbai :

148, Naman Plaza, Behind Shopper's Stop,
S.V. Road, Kandivali(W), Mumbai 400067

Maharashtra.

Tel. : 022 28655050, Fax : 28654949

Vasai :

102, Om Kiram Apt., Janak Puri Complex,
Opp. MSEB Power House, Navghar,
Vasai Road, Dist. Thane - 401 210.

Tel. : 0250 2393935

Chhattisgarth :

Plot No. MIG-63, Kabir Nagar,
Behind Housing Board Office,
Tatibandh, Raipur - 492 002.

Telefax : 0771 2325252

West Africa :

Block No. 2, 1st Floor,
Daimond Bldg., Pati Cherry,
Kollum, Conakry (West Africa)

Tel.: 002 2466201054

email : sales@aarbeequa.com | web : www.aarbeequa.com